

RAMCO



HICEM

Fibre Cement Board

FIBRE CEMENT PLANKS





Ramco Hicem Planks

Ramco Hicem Planks is a fibre cement siding which offers a perfect solution for cladding requirements. These planks are fire resistant, water resistant and termite resistant and have high impact strength which makes them an ideal choice to protect your exterior walls from extreme climatic conditions.

These autoclaved wood grain texture planks give your exterior a stylish finish and enhance the look of your structures. The planks can be coated with acrylic paint to suit your colour preference.



- Wood Grain Texture
- Moisture / Water Resistant
- Solid Toughness
- Excellent Workability
- Low Shrinkage

SPECIFICATIONS

PROPERTIES	UNIT	STANDARD	VALUES
Apparent Density (Dry)	Kg/m ³	IS 14862:2000 & BS EN 12467	> 1200
Water Absorption	%	By weight	~38
Moisture Content (EMC)	%	Ambient	<12
Alkalinity	pH		
Combustibility	-	BS 476:Part 4:1970	Non-combustible
Ignitability	-	BS 476:Part 5:1979	'P' Not Easily Ignitable
Fire Propagation Index	-	BS 476:Part 6:1989	I=0.7
Surface Spread of Flame	-	BS 476:Part 7:1997	Class - 1
Water Impermeability	-	BS EN 12467	Passes
Freeze Thaw Test	-	BS EN 12467	Passes
Warm Water	-	BS EN 12467	Passes
Soak Dry	-	BS EN 12467	Passes
Heat Rain	-	BS EN 12467	Passes
Biological	-	-	No fungus growth
Mould/Fungal Growth	-	IS 4873	Free from Fungal Growth
Termite Resistance	-	IS 4833	No Termite attack
Borer Resistance	-	IS 4873	No Borer Attack
VOC Organic Emission	-	ISO-16000-6	Not Detected
Asbestos Identification	-	X ray Diffraction Method	Free from Asbestos

Finish - Raw Wood
 Profile - Square-cut Edge
 Size(mm) - 150 (H) x 3050 (L) x 8 (THK)

Custom sizes are available at special prices



Natural

Can be coated with acrylic paint to suit your colour preference.



Ruby Red



Black Walnut

APPLICATIONS



Fascias



Eaves & Soffit Lining



Decorative Fences



Gate Cladding



Wall Cladding



External Cladding



IS: 14862 : 2000



CM/L-6700024713



© Copyright 2023 Ramco Industries Limited. All rights reserved. Information given is to the best of our knowledge and belief, accurate and reliable as of the date compiled. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

As our policy of continuous improvement, we reserve the right to modify our specifications any time without notice. Product colours and texture may vary due to climatic conditions or due to limitations in the brochure printing process. Please check the latest version on the website or contact your local Ramco Industries representative.